

# TS DataServer™ for MySQL Quick Start

## Introduction

To install TS DataServer for MySQL, follow these quick and easy steps. Approximately 2 MB is required on the server system.

## CD Installation

Thoroughbred's CD-ROM installation replaces the need for multiple pieces of media.

Installations are accomplished using `cpio`. Before using `cpio` with a CD-ROM drive, the drive must be mounted. A sample mount command follows:

<b>RedHat Linux:</b>	<code>mount -r -t iso9660 /dev/device-name /mountpoint</code>
--------------------------	---

The CD-ROM contains kernel version-specific `cpio` files. The version-specific `cpio` file name should be substituted for the `/dev/device-name` on the `cpio` command. Be sure to include the mountpoint, product platform folder and product file with the `cpio` command. For example, to install the 32-bit product for kernel version 2.6.16:

1. Login as `root`
2. `mount -r -t iso9660 /dev/cdrom /media/cdrom`
3. `cd basic-home-directory`
4. `umask 0`
5. `cpio -ivBmud </media/cdrom/Linux2616_32/tsmy`
6. `./install`

## Getting Started

1. Login as the MySQL administrator.
2. After the MySQL database is up and running, execute `tsmysql`.

## Configuring Clients

1. Update `SERVER.MAP` with Server IDs and TCP/IP addresses.
2. Add Dev line to `IPLINPUT` using the MySQL Server ID found in `SERVER.MAP`
3. Update the Dictionary-IV™ Link Definitions by adding the Server ID and Table Names.